

Overhead Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **Overhead Dead-end**, intended for use on aluminumbased conductor, with a diameter range of .229" to .577", is designed to terminate primary, secondary and neutral wire conductors.

Features

- Tools are not required nor recommended to install Overhead Dead-ends, except for hot stick applications.
- Designed to grip the conductor uniformly to prevent distortion of the conductor.
- Unique design that eliminates bolts, nuts, washers and other component parts that may become lost or damaged during installation or in service.

Documentation

Application Procedures

[SP-2071 \(Overhead Dead-end\)](#)

Catalog Pages

[Overhead Dead-end - Catalog](#)

Part Tables

Catalog Number	Conductor (Inches)		Units	Wt./Lbs.	Length (Inches)	Color Code
	Range	Nominal Size	Per Carton			
OHDE-9534	.229-.257	#4	100	31	24	Orange
OHDE-9536	.290-.325	#2	100	59	30	Red
OHDE-9537*	.326-.364	#1	Obsolete	60	34	Green
OHDE-9538	.365-.409	1/0	50	47	38	Yellow
OHDE-9539	.410-.460	2/0	50	60	38	Blue
OHDE-9540*	.461-.516	3/0	Obsolete	71	45	Orange
OHDE-4577*	.517-.577	4/0	Obsolete	57	52	Red