

Coaxial Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Custom Coaxial and Dual Coaxial Dead-ends are performance-proven dead-end designs for RG-59/U, Dual RG-59/U, Dual RG-6/U and RG-11/U coaxial cable. In addition to the benefits of the basic Telegrip, these premium products feature twin leg construction which cushion and relieve gripping stresses created by unusually high winds and heavy ice loading.

Features

- Feature twin leg construction (cushion and relieve gripping stresses created by unusually high winds and heavy ice loading)
- Especially recommended for foam insulated coaxial cable and areas where there are extreme corrosive and demanding environmental conditions

Documentation

Application Procedures

[SP-2551 \(Coaxial Dead-end\)](#)

Catalog Pages

[Coaxial Dead-end - Catalog](#)

Part Tables

Catalog Number	Cable Type (mm)	Units Per Carton	Wt./Lbs. Per Carton
Custom Coaxial Dead-End			
DE-3329*	RG59/U .242" (6.1)	200	9
Dual Coaxial Dead-End			
DE-2519	DUAL RG59/U .242" X .504" (6.1 x 12.8)	200	20
DE-2520	DUAL RG6/U .275" X .546" (6.9 x 13.8)	200	43
Coaxial Dead-End			
DE-2518	RG11/U .405" (10.2)	200	22

*Manufactured from stainless steel