

Tangent Side Tie: Plastic

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Plastic Tangent Side Ties are intended for use on “tangent” construction with jacketed conductors and side mounted tie top insulators on armless construction. Line or sag angles of up to 15° are recommended.

Features

- Suitable for use with any plastic covered conductor such as Tree Wire or Spacer Cable
- Two versions available: Standard "PVC" and "Semi-Con" for higher voltage applications

Documentation

Application Procedures

[SP-2120 \(Plastic Side Tie\)](#)

Catalog Pages

[Tangent Plastic Side Tie - Catalog](#)

Part Tables

C-Neck

PVC Plastic Ties Catalog Number	Semi-Con Plastic Ties Catalog Number	OD Range (in.)		Nominal Conductor Size	Units per carton	Approx. Wt./Lbs.	Approx. Applied Length (in.)	Insulator Color ID Mark (PVC/SC)	Conductor Color Code (PVC/SC)
		Min.	Max.						
SSC-2150	SSC-2150SC	0.296	0.400	#4, 6/1, 2/64s	100	22	17	Black/None	White
SSC-2151	SSC-2151SC	0.401	0.540	#2, 6/1, 3/64s #4, 7W, 8/64s	100	22	16	Black/None	Green
SSC-2152	SSC-2152SC	0.541	0.730	1/0, 6/1, 10/64s 3/0, 6/1, 4/64s	100	23	16	Black/None	Blue
SSC-2153	SSC-2153SC	0.731	0.920	4/0, 6/1, 10/64s 336.4, 18/1, 6/64s	100	25	18	Black/None	Orange
SSC-2154	SSC-2154SC	0.921	1.100	336.4, 18/1, 10/64s 447, 19W, 8/64s	100	27	19	Black/None	Red
SSC-2155	SSC-2155SC	1.101	1.300	477, 37W, 10/64s 397.5, 19W, 12/64s	100	15	21	Black/None	Black/None

F-Neck

PVC Plastic Ties Catalog Number	Semi-Con Plastic Ties Catalog Number	OD Range (in.)		Nominal Conductor Size	Units per carton	Approx. Wt./Lbs.	Approx. Applied Length (in.)	Insulator Color ID Mark (PVC/SC)	Conductor Color Code (PVC/SC)
		Min.	Max.						
SSF-2250	SSF-2250SC	0.296	0.400	#4, 6/1, 2/64s	50	12	18	Yellow	White
SSF-2251	SSF-2251SC	0.401	0.540	#2, 6/1, 3/64s #4, 7W, 8/64s	50	12	17	Yellow	Green
SSF-2252	SSF-2252SC	0.541	0.730	1/0, 6/1, 10/64s 3/0, 6/1, 4/64s	50	13	17	Yellow	Blue
SSF-2253	SSF-2253SC	0.731	0.920	4/0, 6/1, 10/64s 336.4, 18/1, 6/64s	50	14	19	Yellow	Orange
SSF-2254	SSF-2254SC	0.921	1.100	336.4, 18/1, 10/64s 447, 19W, 8/64s	50	15	20	Yellow	Red
SSF-2255	SSF-2255SC	1.101	1.300	477, 37W, 10/64s 397.5, 19W, 12/64s	50	17	22	Yellow	Black/None

Product Gallery