

Service-Grip Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Service-Grip Dead-end, manufactured of aluminum-covered steel, is designed for bare neutral messengers of self-supporting cable used in making service drops. The Dead-end is recommended for service drops by reason of minimum length, economy, and neatness of appearance. Mechanical strength meets the requirements for NESC Grade "N", Rule 263-E, Supply Services, Spans not exceeding 150 feet.

Features

- Manufactured of aluminum-covered steel
- Designed for bare neutral messengers or self-supporting cable used in making service drops

Documentation

Application Procedures

[SP-2019 \(Service-Grip Dead-end\)](#)

Catalog Pages

[Service-Grip Dead-end - Catalog](#)

Part Tables

Catalog Number	Diameter Range (In.)		Nominal Conductor Sizes				Units	Wt./Lbs.	Length (In.)	Color Code	Max. Neck Dia. (In.)
	Min.	Max.	ACSR	All-Alum.	Alum. Alloy	Comp.	Per Carton				
SG-4500	.169	.198	#6, 6/1	#6, 7W	#6, 7W	#6, 6/1 #6, 7W	300	24	11	Blue	2-3/8
SG-4501	.199	.224	#5, 6/1	#4, Solid	#5, 7W	#4, 7W	300	27	12	White	2-3/8
SG-4502	.225	.257	#4, 6/1 #4, 7/1	#4, 7W	#4, 7W	#4, 6/1 #4, 7/1	300	29	13	Orange	2-3/8
SG-4503	.258	.289	#3, 6/1	#3, 7W #2, Solid	#3, 7W	#3, 6/1 #2, 7W	200	27	14	Black	2-5/8
SG-4504	.290	.325	#2, 6/1 #2, 7/1	#2, 7W	#2, 7W	#2, 6/1 #1, 7W	200	28	15	Red	2-5/8
SG-4505	.326	.360	#1, 6/1	#1, 7W	#1, 7W	#1, 6/1 1/0, 7W	200	31	17	Green	2-5/8
SG-4506	.361	.400	1/0, 6/1	1/0, 7W	1/0, 7W	1/0, 6/1 2/0, 7W	100	28	19	Yellow	2-7/8
SG-4507	.401	.450	2/0, 6/1	2/0, 7W	2/0, 7W	2/0, 6/1 3/0, 7W	100	31	21	Blue	2-7/8
SG-4508	.451	.510	3/0, 6/1	3/0, 7W	3/0, 7W	4/0, 7W	100	33	23	Orange	2-7/8
SG-4509	.511	.580	4/0, 6/1 4/0, 18/1	4/0, 7W	4/0, 7W	4/0, 6/1	100	37	26	Red	3