

Cable Separator Tie

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **Cable Separator Tie** is intended for use on aluminum based conductors with diameters from .245" to .588". Each Cable Separator Tie covers a range of conductor diameters.

Features

- Designed to provide superior mechanical strength and resiliency during conductor motion and cyclic loading conditions.
- Can also be used with cable separators from other manufacturers. Consult Preformed Line Products Company for recommendations.

Documentation

Application Procedures

[SP-2828 \(Cable Separator Tie\)](#)

Catalog Pages

[Cable Separator Tie - Catalog](#)

Part Tables

Catalog Number	Diameter Range (Inches)		Nominal Conductor Size		Units	Wt./ Lbs.	Applied Length (Inches)	Color Code
	Min.	Max.	Bare Conductor	Plastic Jacket Conductor				
CST-4102	.245	.277	#4 (6/1, 7/1) #4 (7W Alum. Alloy)	#6 (7W, 2/64s) #6 (solid 3/64s) #6 (6/1, 2/64s)	100	9	12	Orange
CST-4104	.316	.357	#2 (6/1, 7/1) #2 (7W Alum. Alloy) #1 (6/1)	#4 (7W, 3/64s) #4 (6/1, 7/1, 3/64s)	100	10	14	Red
CST-4105	.358	.405	1/0 (7W All Alum.) 1/0 (6/1) 1/0 (7W Alum Alloy)	#3 (7W, 4/64s) #2 (7W, 3/64s) #4 (7W, 5/64s)	100	12	15	Yellow
CST-4106	.406	.459	2/0 (7W All Alum.) 2/0 (6/1) 2/0 (7W Alum. Alloy)	#2 (6/1, 3/64s) #2 (7W, 4/64s) #1 (7W, 4/64s)	100	14	17	Blue
CST-4107	.460	.520	3/0 (7W All Alum.) 3/0 (6/1) 3/0 (7W Alum. Alloy)	#4 (7W, 8/64s) #1 (6/1, 4/64s) #1 (7W-19W, 5/64s) 1/0 (7W, 4/64s)	100	14	18	Orange
CST-4108	.521	.588	4/0 (7W All Alum.) 4/0 (6/1) 4/0 (7W Alum. Alloy)	1/0 (6/1, 4/64s) 1/0 (7W, 5/64s) 2/0 (7W, 64s) 1/0 (6/1, 5/64s)	100	18	19	Red