

Compression Splice Assembly

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

Compression Splice Assemblies are specially designed for applications on ACSR and ACSS conductors. Designs utilize a dual compression product requiring compression of a steel component around the steel core and an aluminum component around the aluminum wire OD.

Features

- Compression of products can be completed with industry standard presses and dies.
- Aluminum Splice Body: Aluminum component of splice assembly that is compressed around the OD of the conductor.
- Steel Splice Body: Steel component of the splice assembly that is compressed around the OD of the steel core.
- Holding Strength: 95% or more of the conductor rated breaking strength (RBS) in accordance with ANSI C119.4 requirements for tensile strength.
- Designs allows for continuous conductor operating temperatures up to 125°C (150°C two hour emergency).
- Includes: Aluminum splice body, steel splice body, and filler plug.

Documentation

Application Procedures

[SP-3126-2 \(Compression Splice\)](#)

Catalog Pages

[Compression Splice Assembly- CMPSP for ACSR Conductors - Catalog](#)

[Compression Splice Assembly - CMPSP for ACSS and ACSS/TW Conductors - Catalog](#)

Small Catalog

[Compression Hardware Series for ACSR Conductors - EN-CA-1009-1](#)

Part Tables

Splice Assembly Catalog Number	Conductor Information				Al. Body Part No.	Al. Die Size	Steel Splice Part No.	Steel Die Size	Dimensions		Wgt lbs
	Code Word	Area kcmil	Al/St	Dia. in					Al. Tube Length in	Steel Tube Length in	
CMPSP-1063	Tern	795	45/7	1.063	74266	30AH	65595	12SH	27.9	8.5	5.1
CMPSP-1081	Redwing	715.5	30/19	1.081	74267	30AH	65762	12SH	27.9	8.5	5.1
CMPSP-1092	Cuckoo/ Condor	795	24/7,54/7	1.092	74268	30AH	65763	12SH	26.1	8.5	4.8
CMPSP-1108	Drake	795	26/7	1.108	64894	30AH	65542	12SH	26.1	8.5	4.8
CMPSP-1131	Ruddy	900	45/7	1.131	74269	30AH	65765	12SH	28.7	8.5	5.1
CMPSP-1140	Skimmer/ Mallard	795	30/7,30/19	1.140	74270	30AH	65766	12SH	28.7	8.5	5.1
CMPSP-1162	Canary	900	54/7	1.162	74271	30AH	65768	12SH	26.9	8.5	4.9
CMPSP-1165	Corncrake/Rail	954	20/7,45/7	1.165	74272	30AH	65769	12SH	26.9	8.5	4.8
CMPSP-1196	Redbird/ Cardinal	954	24/7,54/7	1.196	74274	30AH	65770	12SH	27.5	8.5	4.9
CMPSP-1203	Snowbird	1033.5	42/7	1.203	74275	30AH	65771	12SH	27.5	8.5	4.9
CMPSP-1212	Ortolan	1033.5	45/7	1.212	74276	34AH	65703	14SH	27.7	8.5	6.9
CMPSP-1245	Curlew	1033.5	54/7	1.245	74277	34AH	65772	14SH	30.3	8.5	7.4
CMPSP-1248	Canvasback	954	30/19	1.248	74278	34AH	65773	14SH	30.3	8.5	7.4
CMPSP-1259	Bluejay	1113	45/7	1.259	74279	34AH	65695	14SH	30.3	8.5	7.3
CMPSP-1293	Finch	1113	54/19	1.293	74280	34AH	65774	14SH	30.9	8.5	7.2
CMPSP-1302	Bunting	1192.5	45/7	1.302	74281	34AH	65693	14SH	30.9	8.5	7.2
CMPSP-1338	Grackle	1192.5	54/19	1.338	74282	36AH	65775	14SH	31.5	8.5	8.1
CMPSP-1345	Bittern	1272	45/7	1.345	74283	36AH	65687	14SH	31.5	8.5	8.1
CMPSP-1504	Lapwing	1590	45/7	1.504	74290	40AH	65683	16SH	33.9	10.3	10.6
CMPSP-1505	Parrot	1510	54/19	1.505	74291	40AH	65782	16SH	33.9	10.3	10.6
CMPSP-1545	Falcon	1590	54/19	1.545	74292	40AH	65675	16SH	45.3	10.3	13.2
CMPSP-1602	Chukar	1780	84/19	1.602	74293	42AH	65539	16SH	45.3	10.3	15.0