

FIBERLIGN[®] Figure 8 Drop Cable Dead-end

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **FIBERLIGN[®] FIGURE 8 Drop Cable Dead-end** has high strength in a light-weight package. Simple to install, the Dead-end is applied on the messenger component of the Figure 8 cable after separating the fiber component at the web. Depending on the jacket adherence, the Dead-end may be applied over the jacket or onto the bare messenger after the jacket is removed.

Features

- Made from corrosion resistant materials that match the messenger strand material
- The loop of the Dead-end will fit over a minimum diameter of 1.0" (25 mm) and a maximum diameter of 1-5/8" (41 mm)
- Designed to fit over common guy wire Dead-end pole fittings

Documentation

Catalog Pages

[Fiberlign Figure 8 Drop DE - Catalog](#)

Part Tables

FIBERLIGN® Figure 8 Drop Cable Dead-ends				
Catalog Number¹	Cable Information²		Color Code	Length Inches
	Dimension³ L x W in. (mm)	Mfg.		
699911619 ⁴	.380 x .160 (9.6 x 4.1)	Corning	Yellow	13"
200811230	.300 x .170 (7.6 x 4.3)	Pirelli	Red	8"

1 Add suffix code "T" to dead-end catalog number to receive P/N 00065474 Thimble. P/N 00065474 is a 1/2" standard thimble – weight is 0.12 lbs. each.

2 Contact PLP for cable applications not shown

3 Dimensions L x W represent Length x Width of the Figure 8.

4 Apply over jacket