

Omni-Seal Closure

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **Omni-Seal Closure** is designed specifically for sub-surface ready access terminal use when a large number of drops will be used. It can accommodate a looped cable up to 1.6" in diameter, six 2-pair service wires and four 5-pair service wires. Drop wire application is permitted during the initial installation, or at a later date for future construction.

Features

- Ideal as a sub-surface terminal when drops are prevalent
- Easily applied, easily re-entered
- Resin filled base and unique sealing system combine to provide a watertight seal
- Available with either a clear cap for immediate visual inspection, or a black cap for direct buried and serial applications
- Durably built to withstand weathering and various soil conditions, even acid and alkali
- Optional terminal block provides for fixed count and pre-stub use
- Kits come complete as ordered

Documentation

Application Procedures

[SP-2747 \(Omni-Seal Closure\)](#)

[SP-2594 \(OMNI-SEAL\)](#)

Catalog Pages

[Omni-Seal Closure - Catalog](#)

MSDS Sheets

[U1-5854 Part A](#)

[U1-5854 Part B](#)

Part Tables

Catalog Number	Description	Standard Carton Qty.
8000557	No Blocks	2 Kits