

Pulling eye

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **Pulling Eye** is designed to provide a functional and safe way of tensioning down guys at the anchor location. It provides a working load of 3,000 lbs with a 5:1 ratio safety factor (Ultimate strength of 15,000 lbs).

Features

- Facilitates safe, fast installation of all dead-ends by a pulling point at the anchor
- Installs around the anchor hardware in seconds
- Nodular Iron housing and keeper with EHS steel bolt and nut
- Corrosion resistant powder coating iron
- Accommodates anchor rods from 1/2" - 1-1/4" (12.7 - 31.75 mm)
- Reusable
- Lightweight

Documentation

Application Procedures

[SP-2013 \(Pulling Eye\)](#)

Catalog Pages

[Pulling Eye - Catalog](#)

Sales Materials

[Pulling Eye - Sell Sheet](#)

Part Tables

Catalog Number	Description	Std. Ctn.
PE-0300	Pulling Eye	4 Units

Replacement Parts

Catalog Number	Description	Std. Ctn.
PE-A-0002	Pulling Eye: Keeper	As Required
PE-B-2019	Pulling Eye: Bolt	As Required
PE-C-0607	Pulling Eye: Nut	As Required
Note: 3,000 lb. working load is based on a 5 to 1 safety factor.		