

# Open Wire Splice

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

**Description**  
**PREFORMED Open Wire Splices** are used for mid-span splicing during new construction and for repair of abraded or severed wire at tie points.

- Features**
- Wrap on easily by hand without a need for wire cutting
  - Designed to permanently restore the full mechanical strength and conductivity of the conductor to which they are applied

**Documentation**  
**Catalog Pages**

[Open Wire Splice - Catalog](#)

**Part Tables**

| Catalog Number      | Wire   |             | Number of Subsets | Length | Color Code | Per Carton |          |
|---------------------|--------|-------------|-------------------|--------|------------|------------|----------|
|                     | Gauge  | Size        |                   |        |            | Units      | Wt./Lbs. |
| Galvanized Steel    |        |             |                   |        |            |            |          |
| GLS-3101            | BWG-12 | .109"       | 3                 | 12"    | Black      | 100        | 9        |
| GLS-3103            | BWG-10 | .134"       | 3                 | 14"    | Orange     | 100        | 15       |
| Aluminum Clad Steel |        |             |                   |        |            |            |          |
| AWLS-5101           | AWG-11 | .091"-.095" | 2                 | 12"    | Green      | 100        | 7        |