

BIRD-FLIGHT™ Diverter

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Description

The **BIRD-FLIGHT Diverter** is designed to make overhead lines and guyed structures visible to birds and provides an economical means of reducing the hazard to both lines and birds.

Features

- Manufactured from gray or yellow high impact PVC with UV protection, aluminum, or galvanized steel
- Additional color/voltage options available (Contact PLP)
- Lightweight
- Easily and quickly installed by hand
- Positive grip on the conductor ensures the BIRD-FLIGHT Diverter remains in the applied location
- Long service life without deterioration of material properties
- Minimal wind resistance
- Recommended spacing distances are 15 foot intervals (depending upon local conditions)

Documentation

Application Procedures

[SP2805 \(BIRD-FLIGHT Diverter\)](#)

[SP3053 \(BIRD-FLIGHT Diverter - Aluminum\)](#)

[SP3427 \(BIRD-FLIGHT Diverter - Galvanized Steel\)](#)

Catalog Pages

[Bird Flight Diverter](#)

[Enviromental catalogue](#)

Sales Materials

[BIRD-FLIGHT Diverter - Sell Sheet](#)

[BIRD-FLIGHT Diverter - Sell Sheet - Special Industries](#)

[Galvanized BIRD-FLIGHT Diverter for Down-Guys - Sell Sheet - Special Industries](#)

Part Tables

CATALOGUE NO.	CONDUCTOR DIAMETER RANGE (mm)
BFD 249-349P/*	6.3 - 8.9
BFD 350-449P/*	9.0 - 11.4
BFD 450-599P/*	11.5 - 15.2
BFD 600-749P/*	15.3 - 19.0

NOTES:

- ADD SUFFIX B, W OR G FOR COLOUR BLACK, WHITE OR GREY RESPECTIVELY
- MATERIAL: UV STABILIZED PVC
- APPROX. WEIGHT: 70 GRAMS

Videos

[INSTALLATION VIDEO](#)